

DHI-PHRIA2.61-RE

General Indoor Rental LED



Features :

- 500x500mm and 500x1000mm cabinet size design, flexibly adapt to multiple scenarios.
- The module supports front and rear maintenance, more convenient operation.
- Quick lock design, Special buckles structural connection between the cabinets, Radians support $-10^{\circ} \sim +10^{\circ}$.
- Support the interconnection of different forms of cabinets and 90° splicing.



Technical Specification

Model

Model	DHI-PHRIA2.61-RE
-------	------------------

Parameters

Pixel Pitch	2.604mm
Pixel Type	1R1G1B
Pixel Configuration	SMD1515
Brightness(Max)	1000 nit
Color Temperature	6500K-9300K (adjustable)
Viewing Angle	H160°/V140°
Pixel Density	147,456 dots/m ²
Module Size	W250mmxH250mm
Module Resolution	96x96 dots
Cabinet Size	W500xH500xD83mm
Cabinet Resolution	192x192 dots
Cabinet Weight	8kg ± 0.5
Cabinet Material	Die-cast aluminum

Cabinet Aspect Ratio	1:1
IP Rating	Front IP20/Rear IP20
Operating Temperature/Humidity	-10 C~+40 C /10%~80%RH
Storage Temperature/Humidity	-20 C~+60 C /10%~80%RH
Gray Scale	14 bits
Contrast Ratio	5000:1
Refresh Rate	3840 Hz
Input power frequency	50/60 Hz
Input Voltage	AC110~220V (+/-10%)
Input Power (Max)	500 W/ m ²
Input Power (Avg)	180 W/ m ²
Installation Mode	Floor Mounted/Hanging
Maintenance Mode	Front & Rear maintenance
Signal Transmission Distance	CAT5 Cable (L≤100m), multi-mode fiber (L≤300m), single mode fiber (L≤10km)

DHI-PHRIA2.61-RE

General Indoor Rental LED

